



Epson TM-T88VI

Reliable, ultra-fast reciept printer with state of the art mobile connectivity

Connect to multiple devices simultaneously

Ultrafast print speed of up to 350 mm/s

Reliability you can count on

Easy printing from mobile devices

Print from web-based applications

Triple interface connectivity to future proof growing businesses

Industry leading four year warranty

Epson TM-T88VI

Product Specifications			
PAPER		COLOUR	Black / White
PAPER SIZE	80 mm: 79.50 ± 0.50 (W) mm x dia 83.00 mm	INSTALLATION	Horizontally, wall hanging
	58 mm: 57.50 ± 0.50 (W) mm x dia 83.00 mm	INTERFACE CONNECTORS	D.K.D. function
FONTS & STYLES		HUMIDITY	Operation 10% - 90%
PRINT SPEED	350 mm/s	TEMPERATURE	Operation 5 °C - 45 °C, Storage -10 °C - 50 °C
PRINT SPEED (DEFAULT)	300 mm/s	STANDARD COMPLIANCE	
PRINTING FONT	Font A (default): 12 x 24	SAFETY APPROVALS	RCM: AS / NZS CISPR class A
	Font B: 9 x 17 (including 2-dot horizontal spacing)	OTHER	
COLUMN CAPACITY RECIEPT	80 mm: 42/48/56 columns	WARRANTY	48 months
CHARACTER SIZE	58 mm: 30/36/40 columns Font A: 1.41 x 3.39 (W x H mm)	WHAT'S IN THE BOX	
OTATIAOTETI SIZE	Font B: 0.99 x 2.40 (W x H mm)		Connector cover
CHARACTER SET	95 Alphanumeric, 18 set International, 128 x 43 Graphic		Main unit
PRINTING CHARACTERS	Text (incl. Euro symbol), Graphics, Barcode		PS-180 & AC cable
INTERFACES	(Paper spacer
CONNECTIVITY	Built-in USB, Built-in Ethernet (10/100Base-T/TX) +		Power switch cover
	UIB (Serial, Parallel, Powered USB)		Roll paper Setup quide
	Bluetooth 2.1+EDR (dedicated model)		Warranty document
	Wireless (USB wireless dongle): OT-WL05 (802.11	OPTIONAL ACCESSORIES	warranty document
	a/b/g/n) or OT-WL02 (802.11 b/g/n)	C32C845040	WH-10 (040) Wall hanging bracket
	Beacon (using Bluetooth low energy): Beacon dongle	C32C890739	OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz
DATA BUEFER	(Epson approved dongle: Laird model BT-820)	C32C814596	Power supply cover
DATA BUFFER DATA BUFFER	45 Bytes or 4 kb, selectable		1 Owor Supply Sover
POWER	45 Dytes of 4 kb, selectable	CONFIG BUILDS C31CE94241	TM-T88VI-241 Built-in ethernet, USB, serial,
POWER SUPPLY	PS-180, AC cable	C31CE94241	dark grey
OPERATING VOLTAGE	24 V	C31CE94243	TM-T88VI-243 Built-in ethernet, USB, parallel,
POWER CONSUMPTION	Operating: 27.6 W	0310194243	gark grey
	Stand by: 0.5 W	C31CE94581	TM-T88VI-581 Built-in ethernet, USB, BT-iOS
GENERAL			dark grey
PRODUCT DIMENSIONS	145 x 195 x 148 mm (Width x Depth x Height)	COVER PLUS (OPTIONAL)	
PRODUCT WEIGHT	1.6 kg	1YWT88VI	CoverPlus 1yr service pack TM-T88VI
			· · · · · · · · · · · · · · · · · ·

Better Products for a Better Future











Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

05/19

EPSON AUSTRALIA

3 Talavera Road North Ryde NSW 2113 Tel: 1300 361 054 www.epson.com.au

EPSON NEW ZEALAND

Level 2 7-9 Fanshawe Street Auckland, 1010 Tel: 088 237 766 www.epson.co.nz





