Technical Specifications

HP E24mv G4 FHD Conferencing Monitor



- 1. Microphones (2)
- 2. Camera Light
- 3. RGB Lens
- 4. IR Lights


Front

- 5. Audio Buttons
- 6. OSD Buttons
- 7. Power Button



Technical Specifications

HP E24mv G4 FHD Conferencing Monitor



- 1. Security Cable Slot
- 2. Power Connector
- 3. DisplayPort[™]
- 4. HDMI Port

- Back
- 5. VGA Port
- 6. USB-B Port
- 7. USB-A Ports (2)



Technical Specifications

| Panel Specifications | Dicplay Size (Diagonal) | 22.0" |
|------------------------|--|--|
| Pallet Specifications | Display Size (Diagonal) Panel Technology | 23.8" IPS |
| | Max Refresh Rate | 60 Hz |
| | Native Resolution | 1920x1080 |
| | Panel Bit Depth | 8 bit (6bit + FRC) |
| | Aspect Ratio | 16:9 |
| | Brightness (Typical) | 250 nits |
| | Contrast Ratio (Static) | 1000:1 |
| | Dynamic Contrast Ratio | 5M:1 |
| | Flicker Free | Yes |
| | Pixel Pitch | 0.2745 x 0.2745mm |
| | Pixels Per Inch (PPI) | 93 PPI |
| | Backlight Lamp Life Minimum (To Half | 30k |
| | Brightness - In Hours) | 504 |
| | Backlight Type | Edge-lit |
| | Screen Treatment | Anti-glare |
| | Hardness | 3H |
| | Haze | 25% |
| | Response Time (Typical) | 5ms GtG (with overdrive) |
| | Horizontal Viewing Angle (Typical Cr>10) | 178° |
| | Vertical Viewing Angle (Typical Cr>10) | 178° |
| | Panel Active Area Metric (W X H) | 52.70 x 29.65 cm |
| | Panel Active Area Imperial (W X H) | 20.75 x 11.67 in |
| | - | he Typical Specifications Provided By HP's Component |
| | Manufacturers; Actual Performance May Vary E | ither Higher Or Lower. |
| Color Management | Color Space/ Subsampling Support | NTSC 72% / RGB 4:4:4 |
| | RGB Channel Adjust | Yes, Gain |
| | Default Color Temperature | Neutral(6500K) |
| Monitor Specifications | Bezel Type | 3-sided Micro Edge |
| | Color Of Stand | Sliver Stand, Black Head |
| | Color Of Head | Black |
| | Tilt | -5 to +23° |
| | Swivel | ±45° |
| | Pivot | ±90 |
| | Height Adjust Range | 150mm |
| | Vesa Mounting | 100 mm x 100 mm |
| | Security Lock | Standard Security Lock Slot |
| | Detachable Stand | Yes |
| | Warranty | 3 years |
| | Low Blue Light | Yes, HP Eye Ease (Eyesafe® Certified) |
| | Webcam | 5 MP |
| | Windows Hello Compatible | Yes |
| | Microphone | Yes |
| | Speaker Output Power | 2 x 2W |
| | Conferencing Hot Keys | Mic mute, Speaker Mute, Volume Up/Down – |
| | Compatible Collaboration Software | Zoom |



HP E24mv G4 FHD Conferencing Monitor

QuickSpecs

Technical Specifications

| | Display Software On Screen Display Native Resolution Maximum Resolution Preset Graphic Modes/Supported Resolutions | HP Display Center Button Full HD (1920 x 1080) 1920×1080 @ 60HZ 640 x 480 @ 60HZ 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @ 60 Hz |
|---|---|--|
| | Minimum Vertical Scan Rate | 50 Hz |
| | Maximum Vertical Scan Rate | 60 Hz |
| | Minimum Horizontal Scan Rate | 30.0 kHz |
| | Maximum Horizontal Scan Rate | 80.0 kHz |
| | Maximum Pixel Clock | 170.0 MHz |
| | User Programmable Modes | Yes, 10 |
| | Languages | 10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese) |
| Connector Types | DisplayPort™ | 1 DisplayPort [™] 1.2 |
| | | 1 HDMI 1.4 |
| | USB-A | 4 USB-A 3.1 Gen 1 |
| | USB-B (Hub enablement) VGA | 1 USB-B |
| | vga Audio Port | 1 VGA |
| | Αυαίο Ρογτ | 1 Headphone Out Combo Jack |
| Special Features | Remote Manageability | No |
| | User Updateable Firmware | Yes |
| Power & Operating | Power Supply | Internal |
| Specs | Power Source | 100 – 240 VAC 50/60 Hz |
| | Power Consumption- MAX | 50 W |
| | Energy Saving/Stand By Mode | 0.5 W |
| | Power Consumption- Typical | 28 W |
| ENERGY STAR Data | Operational Mode at 100 VAC | 13.2 W |
| | Operational Mode at 115 VAC | 13 W |
| | Operational Mode at 230 VAC | 13.2 W |
| EU Energy Efficiency Class (ERP lot-5) | On-mode Power Consumption | 16 W |
| - | Energy Efficiency Class | E |
| Operating Conditions | Operating Temperature - Celsius | 5° – 35°C |



Technical Specifications

| | Operating Temperature - Fahrenheit Non-operating Temperature - Celsius Non-operating Temperature - Fahrenheit | 41° – 95°F –34° – 60°C 29° – 140°F | | | |
|--|--|--|-------------------------|--|--|
| | Operating Humidity Non-operating Humidity | 20 – 80% Relative Humidity (non-condensing) 5 – 95 % 0 – 5,000 m (16,400 ft.) 0 – 12.192 m (40,000 ft.) | | | |
| | Operating Altitude Non-operating Altitude | | | | |
| Environmental Features and | Mercury-free LED display backlighting Arsenic-Free Display Glass | Yes, Mercury-free LED backlights Yes Yes WW application | | | |
| Certifications | Low Halogen | | | | |
| | Agency Approvals And Certifications | CE,CB,KC/KCC/NOM/PSB/EAC/GS/TUV-S/ISO 9241-307/ Low Blue Light/ BIS/cTUVus/CCC/CEL/CECP/SEPA/Energy Star/TCO/TCO Certified Edge/VCCI/FCC/BSMI/Vietnam MEPS/Australian-New Zealand MEPS/WEEE/UAE/Ukraine | | | |
| | Microsoft WHQL Certification | Yes | | | |
| | ENERGY STAR [®] Certified | Yes | | | |
| | EPEAT® Registered Regions need to verify by country | Yes | | | |
| | China Energy Label | CEL Grade 1 | | | |
| | TCO Certified Edge | Yes | | | |
| | TCO Certified | Yes | | | |
| | SmartWay Transport Partnership - NA only | Yes (NA sku) | | | |
| Contains Recycled Plastics | Contains Recycled Plastics | ABS 85% | | | |
| | Recyclable Packaging (Box, packing materials) | 100% fiber packaging, cardboard | | | |
| Unit Product/Package Specifications | Product Dimensions (Unpacked with stand) (W x D x H) | 53.94 x 21.6 x 53.07 cm | 21.23 x 8.5 x 20.9 in | | |
| | Product Dimensions (Packed) (W x D x H) | 59.6 x 41.1 x 22.5 cm | 23.46 x 16.18 x 8.86 in | | |
| | Display Head Dimensions (Unpacked without stand) (W x D x H) | 53.94 x 4.7x 35.56 cm | 21.23 x 1.85 x 17.78 in | | |
| | Base Area Footprint (w x d mm) | 288 x 216 mm | 11.38 x 8.5 in | | |
| | Bezel Measurements - Metric | Bottom: 52 mm | Bottom: 2.04 in | | |
| | Product Weight (Unpacked with stand) | 6.5 kg | 14.3 lb | | |
| | Product Weight (Packed) | 10.4kg | 22.9 lb | | |
| | Product Weight (Head Only) | 3.9 kg | 8.6 lb | | |



Technical Specifications

What's in the box?

AC power cord (1.83m) 5.9 ft HDMI Cable (1.8m) 5.9 ft DP Cable (1.8m) 5.9 ft USB A-B cable (1.8m) 5.9 ft QS Doc Kit

User Guide and Warranty Languages

User Guide Languages

Warranty Languages

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.



Technical Specifications

Copyright © 2021 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



Change Log

| V1 | to V2 | | |
|----|-------|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

